

ACME MINI STEP


Φ36 Engine Wall /Path Light



cutout:36mm



Wall Wash Optic



Accessories not included

Concrete recessing kit

Designed for super eye comfort,
minimum glare




bezel




Black Painted

IP Rating:	IP20
Optics:	Asymmetrical Wallwash
UGR:	<10
CRI:	92Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	3000K/3500K
Typical Source	
Efficacy (lm/W):	103
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 3V 300mA 1.3W DC 3V 650mA 3W
Ambient temp:	-20 °C to 45 °C
Class:	II
Ceiling Thickness:	5mm-28mm
Material:	Fine aluminium 6063A



3W Ra92 3000K
Asymmetrical

h(m)	E(lx)	D(m)
0.5	130	0.47
1.0	33	0.94
1.5	14	1.41
2.0	8	1.88
2.5	5	2.35
3.0	4	2.82



W system	lm system	optics	code
1.3W	31	Asymmetrical Wallwash	MFL361.3W-30NWS-B
3W	52	Asymmetrical Wallwash	MFL3603W-30NWS-B