

ACME SPY

Φ50 In/out Spotlights



cutout:50mm



Adjustable Optic




matt white painted




matt black painted



Recessed Trim



Recessed Trimless



IP Rating:	IP20 and IP44 options
Optics:	15°/28°/36°
UGR:	< 10
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K/3500K/4000K/5000K/ 2000K-3000K/1800K-4000K/2700K-6000K

Typical Source

Efficacy (lm/W):

110

Control:

On/off, Mains Dim, 0/1- 10V, Dali, Zigbee, Casambi

Binning

2 Step MacAdams

Input:

AC220-240V 50/60Hz

Output:

DC 36V 150mA 6W

Ambient temp:


-20 °C to 45 °C

Class:

II


Material:

Fine aluminium 6063A




6W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	4937	0.14
1.0	1234	0.27
1.5	549	0.41
2.0	309	0.54
2.5	197	0.68
3.0	137	0.81



6W Ra98 3000K 28°

h(m)	E(lx)	D(m)
0.5	2848	0.25
1.0	712	0.49
1.5	316	0.74
2.0	178	0.98
2.5	114	1.23
3.0	79	1.47



6W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	1706	0.31
1.0	426	0.62
1.5	190	0.93
2.0	107	1.25
2.5	68	1.56
3.0	47	1.87



DuraGreen project:
Stellar Works Flagship Showroom



W system	lm system	optics	code
6W	373	15°	AFL5006W-IO-30N15-B
6W	445	28°	AFL5006W-IO-30N28-B
6W	446	36°	AFL5006W-IO-30N36-B



W system	lm system	optics	code
6W	373	15°	AFL5006W-IO-TL-30N15-B
6W	445	28°	AFL5006W-IO-TL-30N28-B
6W	446	36°	AFL5006W-IO-TL-30N36-B

Designed with ease and convenience in mind, these fixtures feature a user-friendly pull mechanism that enables your favorite pieces, artwork, or decor to be highlighted. From sculptures to paintings, let ACME SPY bring your treasures to life with precise, targeted radiance, adding both function and form to your stylish space.



DuraGreen project:
AXENT Showroom