

ACME SPY

Φ78 In/out Spotlights



cutout:78mm



Adjustable Optic




matt white painted


matt black painted



Recessed Trim



Recessed Trimless



IP Rating:	IP20 and IP44 options
Optics:	15°/24°/36°/50°
UGR:	< 10
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K/3500K/4000K/5000K/ 2000K-3000K/1800K-4000K/2700K-6000K

Typical Source

Efficacy (lm/W): 110

Control: On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi

Binning 2 Step MacAdams


Input: AC220-240V 50/60Hz

Output: DC 36V 250mA 10W

Ambient temp: -20 °C to 45 °C


Class: II

Material: Fine aluminium 6063A




10W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	8822	0.15
1.0	2206	0.30
1.5	980	0.45
2.0	551	0.60
2.5	353	0.76
3.0	245	0.91




10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	6615	0.23
1.0	1654	0.46
1.5	735	0.69
2.0	413	0.92
2.5	265	1.15
3.0	184	1.37



10W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	3458	0.32
1.0	864	0.65
1.5	384	0.97
2.0	216	1.29
2.5	138	1.61
3.0	96	1.94



10W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	2048	0.45
1.0	512	0.89
1.5	228	1.34
2.0	128	1.79
2.5	82	2.24
3.0	57	2.68



DuraGreen project:
MESTRE Showroom



W system	lm system	optics	code
10W	501	15°	AFL7810W-IO-30N15-B
10W	653	24°	AFL7810W-IO-30N24-B
10W	692	36°	AFL7810W-IO-30N36-B
10W	676	50°	AFL7810W-IO-30N50-B



W system	lm system	optics	code
10W	501	15°	AFL7810W-IO-TL-30N15-B
10W	653	24°	AFL7810W-IO-TL-30N24-B
10W	692	36°	AFL7810W-IO-TL-30N36-B
10W	676	50°	AFL7810W-IO-TL-30N50-B

Designed with ease and convenience in mind, these fixtures feature a user-friendly pull mechanism that enables your favorite pieces, artwork, or decor to be highlighted. From sculptures to paintings, let ACME SPY bring your treasures to life with precise, targeted radiance, adding both function and form to your stylish space.



DuraGreen project:
AXENT Showroom