

BELLA


Φ41 Surface Zoomable 20°-50° Wall Fixtures/Ceilings




Adjustable Optic



- White Painted
- Black Painted
- Antique Bronze
- Brushed Grey




2Spots Surface




3Spots Surface

IP Rating:	IP20
Optics:	Zoomable 20°-50°
UGR:	<17
CRI:	92Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	3000K/3500K/2700-6000K
Typical Source Efficacy (lm/W):	96
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 12V 600mA 8Wx2 / 8Wx3
Ambient temp:	-20 C to 45 C
Class:	II
Material:	Fine aluminium 6063A




8W Ra92 3000K 20°

h(m)	E(lx)	D(m)
0.5	2978	0.21
1.0	745	0.42
1.5	331	0.63
2.0	186	0.84
2.5	119	1.04
3.0	83	1.25



8W Ra92 3000K 30°

h(m)	E(lx)	D(m)
0.5	1805	0.30
1.0	451	0.59
1.5	201	0.89
2.0	113	1.18
2.5	72	1.48
3.0	50	1.78



8W Ra92 3000K 50°

h(m)	E(lx)	D(m)
0.5	795	0.49
1.0	199	0.97
1.5	88	1.46
2.0	50	1.94
2.5	32	2.43
3.0	22	2.91



W system	lm system	optics	code
8W*2	388*2-385*2	20°- 50°	ST24108WX2-30N2050-B



W system	lm system	optics	code
8W*3	388*3-385*3	20°- 50°	ST34108WX3-30N2050-B