


Φ73
Surface Adjustable Light



Adjustable Optic




White Painted



Black Painted




IP Rating:	IP20 and IP44 options
Optics:	24°/36°
UGR:	< 10
CRI:	98Ra
Lifetime:	> 50,000 hrs (L70 B10)
CCT:	2700K/3000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning:	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W DC 36V 300mA 12W
Ambient temp:	-20 °C to 45 °C
Class:	II



12W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	6463	0.24
1.0	1616	0.48
1.5	718	0.72
2.0	404	0.96
2.5	259	1.20
3.0	180	1.44




12W Ra98 3000K 36°


h(m)	E(lx)	D(m)
0.5	4042	0.31
1.0	1011	0.62
1.5	449	0.93
2.0	253	1.25
2.5	162	1.56
3.0	112	1.87




DuraGreen project:
Curio Resort by Hilton Hotel




W system	lm system	optics	code
6W	311	24°	MFS7306W-30N24-B
6W	315	36°	MFS7306W-30N36-B



W system	lm system	optics	code
8W	444	24°	MFS7308W-30N24-B
8W	422	36°	MFS7308W-30N36-B



W system	lm system	optics	code
10W	518	24°	MFS7310W-30N24-B
10W	508	36°	MFS7310W-30N36-B



W system	lm system	optics	code
12W	567	24°	MFS7312W-30N24-B
12W	612	36°	MFS7312W-30N36-B