

SYSTEM 68


Φ68 ACME Downlight Trimless Adjustable Wall-Washer



cutout :68mm



Wall Wash Optic



baffle



Black Painted
9005



White Painted
9016



Bespoke

IP Rating:

IP65 Front

Optics:

Asymmetrical Wallwash

UGR:

<10

CRI:

98Ra

Lifetime:

>50,000 hrs (L70 B10)

CCT:

2700K/3000K

Typical Source

Efficacy (lm/W):

110

Control:

On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi

Binning

2 Step MacAdams

Input:

AC220-240V 50/60Hz

Output:

DC 36V 350mA 15W

Ambient temp:

-20 °C to 45 °C

Class:

II

Material:


Fine aluminium 6063A

Fire resistance test:

60 minutes


Certification:

CB/CE/UKCA/GLOBAL MARK/60-MINUNTE FIRE RESISTANCE



15W Ra98 3000K
Asymmetrical

h(m)	E(lx)	D(m)
0.5	50	0.82
1.0	12	1.64
1.5	6	2.46
2.0	3	3.27
2.5	2	4.09
3.0	1	4.91



X = distance to wall
= ceiling height ÷ 3



W system	lm system	optics	code
15W	448	Asymmetrical Wallwash	MFL6815W-TL-30NWS