

SYSTEM 78



Φ78 BELLA Zoom Long Snoot Downlight Trimless Adjustable Downlight



cutout :78mm



Adjustable Optic



baffle

Black Painted
9005

White Painted
9016

Signature Metal Finishes

Polished
Brass


Antique
Brass

Copper
Bronze

Aged
Brass


Bright
Chrome

IP Rating:	IP20 and IP44 options
Optics:	Zoomable 20°-50°
UGR:	<10
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 250mA 10W
Ambient temp:	-20 °C to 45 °C
Class:	II
Optional accessories:	Honeycomb louvre, Solite Lense, Spread Lense, Colour Filter
Material:	Fine aluminium 6063A
Certification :	CB/CE/UKCA/GLOBAL MARK



10W Ra98 3000K 20°

h(m)	E(lx)	D(m)
0.5	4916	0.20
1.0	1229	0.40
1.5	546	0.59
2.0	307	0.79
2.5	197	0.99
3.0	137	1.19



10W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	1480	0.44
1.0	370	0.88
1.5	164	1.32
2.0	92	1.76
2.5	59	2.21
3.0	41	2.65



W system	lm system	optics	code
10W	703-690	20°- 50°	AFL7810W-LS-TL-30N2050