

# SYSTEM 36

## Φ41 BELLA Zoomable Pendant Mini-Trim Pendant



cutout: 40mm




Antique Bronze




Bespoke

|                                        |                                                   |
|----------------------------------------|---------------------------------------------------|
| <b>IP Rating:</b>                      | IP20                                              |
| <b>Optics:</b>                         | Zoomable 20°-50°                                  |
| <b>UGR:</b>                            | <17                                               |
| <b>CRI:</b>                            | 92Ra                                              |
| <b>Lifetime:</b>                       | >50,000 hrs (L70 B10)                             |
| <b>CCT:</b>                            | 2700K/3000K                                       |
| <b>Typical Source Efficacy (lm/W):</b> | 96                                                |
| <b>Control:</b>                        | On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi |
| <b>Binning</b>                         | 2 Step MacAdams                                   |
| <b>Input:</b>                          | AC220-240V 50/60Hz                                |
| <b>Output:</b>                         | DC 12V 600mA 8W                                   |
| <b>Ambient temp:</b>                   | -20 °C to 45 °C                                   |
| <b>Class:</b>                          | II                                                |
| <b>Ceiling Thickness:</b>              | 5mm-28mm                                          |
| <b>Material:</b>                       | Fine aluminium 6063A                              |




8W Ra92 3000K 20°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 0.5  | 2978  | 0.21 |
| 1.0  | 745   | 0.42 |
| 1.5  | 331   | 0.63 |
| 2.0  | 186   | 0.84 |
| 2.5  | 119   | 1.04 |
| 3.0  | 83    | 1.25 |



8W Ra92 3000K 30°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 0.5  | 1805  | 0.30 |
| 1.0  | 451   | 0.59 |
| 1.5  | 201   | 0.89 |
| 2.0  | 113   | 1.18 |
| 2.5  | 72    | 1.48 |
| 3.0  | 50    | 1.78 |



8W Ra92 3000K 50°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 0.5  | 795   | 0.49 |
| 1.0  | 199   | 0.97 |
| 1.5  | 88    | 1.46 |
| 2.0  | 50    | 1.94 |
| 2.5  | 32    | 2.43 |
| 3.0  | 22    | 2.91 |



DuraGreen project:  
Home in Rome



| <b>W system</b> | <b>lm system</b> | <b>optics</b> | <b>code</b>      |
|-----------------|------------------|---------------|------------------|
| 8W              | 388-385          | 20°- 50°      | RTP4108W-30N2050 |