

SYSTEM 36


Φ41 BELLA Zoomable Spotlight Trimless Adjustable Spotlight



cutout :36mm



Adjustable Optic



White Painted



Black Painted



Bespoke

IP Rating:

IP20

Optics:

Zoomable 20°-50°

UGR:

< 17

CRI:

92Ra

Lifetime:

>50,000 hrs (L70 B10)

CCT:

2700K/3000K

Typical Source

Efficacy (lm/W):

96

Control:

On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi

Binning

2 Step MacAdams

Input:

AC220-240V 50/60Hz

Output:

DC 12V 350mA 6W

Ambient temp:

-20 °C to 45 °C

Class:


II

Material:

Fine aluminium 6063A


Certification :

CB/CE/UKCA/GLOBAL MARK




6W Ra92 3000K 20°

h(m)	E(lx)	D(m)
0.5	2355	0.20
1.0	589	0.40
1.5	262	0.59
2.0	147	0.79
2.5	94	0.99
3.0	65	1.19



6W Ra92 3000K 30°

h(m)	E(lx)	D(m)
0.5	1378	0.29
1.0	344	0.58
1.5	153	0.88
2.0	86	1.17
2.5	55	1.46
3.0	38	1.75



6W Ra92 3000K 50°

h(m)	E(lx)	D(m)
0.5	616	0.47
1.0	154	0.95
1.5	68	1.42
2.0	38	1.90
2.5	25	2.37
3.0	17	2.85



DuraGreen project:
Valcucine Flagship Store, Tianjin



W system	lm system	optics	code
6W	292-296	20°- 50°	TL4106W-30N2050