

SYSTEM 68


Φ68 GLAMO Zoomable Spotlight Trimless Adjustable Spotlight



cutout :68mm



Adjustable Optic



matt white painted

matt black painted



Bespoke

IP Rating:

IP20 and IP44 options

Optics:

Zoomable 15°-50°

UGR:

<17

CRI:

98Ra

Lifetime:

>50,000 hrs (L70 B10)

CCT:

2700K/3000K

Typical Source

Efficacy (lm/W):

110

Control:

On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi

Binning:

2 Step MacAdams

Input:

AC220-240V 50/60Hz

Output:

DC 36V 300mA 12W

Ambient temp:

-20 °C to 45 °C

Class:


II

Material:

Fine aluminium 6063A


Certification:

CB/CE/UKCA/GLOBAL MARK



12W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	12099	0.14
1.0	3025	0.27
1.5	1344	0.41
2.0	756	0.54
2.5	484	0.68
3.0	336	0.81



12W Ra98 3000K 40°

h(m)	E(lx)	D(m)
0.5	2174	0.38
1.0	544	0.76
1.5	242	1.14
2.0	136	1.52
2.5	87	1.90
3.0	60	2.28



The Anatomy of Persephone
GARETH TRISTAIN EDWARDS
In layers (Shellac on Edelman's)
Acrylic, enamel, gold leaf, ink, 2D relief, blue
gilt, copper and varnished silver leaf, glass
Box 1000 x 700 mm
£1995 bankcontemporary.com

DuraGreen project:
Showroom in London



W system	lm system	optics	code
12W	756-747	15°- 50°	TL6812W-30N1550